




# EASTON - Pfeiltabellen

COMPOUND BOW - Release Aid Calculated Peak Bow Weight - Lbs.			CORRECT ARROW LENGTH FOR TARGET • FIELD • 3D											RECURVE BOW Bow Weight - Lbs. Finger Release
Soft Cam  ATA up to 210 FPS IBO up to 260 FPS	Medium Cam  ATA 211-230 FPS IBO 261-290 FPS	Single or Hard Cam  ATA 231 FPS up IBO 291 FPS up	22½ (57.2 cm) <b>23"</b> 23½ (59.7 cm)	23½ (59.7 cm) <b>24"</b> 24½ (62.2 cm)	24½ (62.2 cm) <b>25"</b> 25½ (64.8 cm)	25½ (64.8 cm) <b>26"</b> 26½ (67.3 cm)	26½ (67.3 cm) <b>27"</b> 27½ (69.9 cm)	27½ (69.9 cm) <b>28"</b> 28½ (72.4 cm)	28½ (72.4 cm) <b>29"</b> 29½ (75.0 cm)	29½ (75.0 cm) <b>30"</b> 30½ (77.5 cm)	30½ (77.5 cm) <b>31"</b> 31½ (80.0 cm)	31½ (80.0 cm) <b>32"</b> 32½ (82.5 cm)		
29-35 lbs. (13.2-15.9 kg)								<b>T1</b>	<b>T2</b>	<b>T3</b>				<b>17-23 lbs.</b> (7.7-10.4 kg)
35-40 lbs. (15.9-18.1 kg)	29-35 lbs. (13.2-15.9 kg)					<b>T1</b>	<b>T2</b>	<b>T3</b>	<b>T4</b>	<b>T5</b>				<b>24-29 lbs.</b> (10.9-13.2 kg)
40-45 lbs. (18.1-20.4 kg)	35-40 lbs. (15.9-18.1 kg)	29-35 lbs. (13.2-15.9 kg)			<b>T1</b>	<b>T2</b>	<b>T3</b>	<b>T4</b>	<b>T5</b>	<b>T6</b>	<b>T7</b>			<b>30-35 lbs.</b> (13.6-15.9 kg)
45-50 lbs. (20.4-22.7 kg)	40-45 lbs. (18.1-20.4 kg)	35-40 lbs. (15.9-18.1 kg)		<b>T1</b>	<b>T2</b>	<b>T3</b>	<b>T4</b>	<b>T5</b>	<b>T6</b>	<b>T7</b>	<b>T8</b>	<b>T9</b>		<b>36-40 lbs.</b> (16.3-18.1 kg)
50-55 lbs. (22.7-24.9 kg)	45-50 lbs. (20.4-22.7 kg)	40-45 lbs. (18.1-20.4 kg)	<b>T1</b>	<b>T2</b>	<b>T3</b>	<b>T4</b>	<b>T5</b>	<b>T6</b>	<b>T7</b>	<b>T8</b>	<b>T9</b>	<b>T10</b>		<b>41-45 lbs.</b> (18.6-20.4 kg)
55-60 lbs. (24.9-27.2 kg)	50-55 lbs. (22.7-24.9 kg)	45-50 lbs. (20.4-22.7 kg)	<b>T2</b>	<b>T3</b>	<b>T4</b>	<b>T5</b>	<b>T6</b>	<b>T7</b>	<b>T8</b>	<b>T9</b>	<b>T10</b>	<b>T11</b>		<b>46-50 lbs.</b> (20.9-22.7 kg)
60-65 lbs. (27.2-29.5 kg)	55-60 lbs. (24.9-27.2 kg)	50-55 lbs. (22.7-24.9 kg)	<b>T3</b>	<b>T4</b>	<b>T5</b>	<b>T6</b>	<b>T7</b>	<b>T8</b>	<b>T9</b>	<b>T10</b>	<b>T11</b>	<b>T12</b>		<b>51-55 lbs.</b> (23.1-24.9 kg)
65-70 lbs. (29.5-31.8 kg)	60-65 lbs. (27.2-29.5 kg)	55-60 lbs. (24.9-27.2 kg)	<b>T4</b>	<b>T5</b>	<b>T6</b>	<b>T7</b>	<b>T8</b>	<b>T9</b>	<b>T10</b>	<b>T11</b>	<b>T12</b>	<b>T13</b>		<b>56-60 lbs.</b> (25.4-27.2 kg)
70-76 lbs. (31.8-34.5 kg)	65-70 lbs. (29.5-31.8 kg)	60-65 lbs. (27.2-29.5 kg)	<b>T5</b>	<b>T6</b>	<b>T7</b>	<b>T8</b>	<b>T9</b>	<b>T10</b>	<b>T11</b>	<b>T12</b>	<b>T13</b>	<b>T13</b>		<b>61-65 lbs.</b> (27.7-29.5 kg)
76-82 lbs. (34.5-37.2 kg)	70-76 lbs. (31.8-34.5 kg)	65-70 lbs. (29.5-31.8 kg)	<b>T6</b>	<b>T7</b>	<b>T8</b>	<b>T9</b>	<b>T10</b>	<b>T11</b>	<b>T12</b>	<b>T13</b>	<b>T13</b>	<b>T14</b>		<b>66-70 lbs.</b> (29.9-31.8 kg)
82-88 lbs. (37.2-39.9 kg)	76-82 lbs. (34.5-37.2 kg)	70-76 lbs. (31.8-34.5 kg)	<b>T7</b>	<b>T8</b>	<b>T9</b>	<b>T10</b>	<b>T11</b>	<b>T12</b>	<b>T13</b>	<b>T13</b>	<b>T14</b>			<b>71-76 lbs.</b> (32.2-34.5 kg)

No X10 or A/C/E shafts suitable in shaded areas above.

Size	Spine	Model	Weight Grs/Inch	Wt @29"	Size	Spine	Model	Weight Grs/Inch	Wt @29"	Size	Spine	Model	Weight Grs/Inch	Wt @29"	Size	Spine	Model	Weight Grs/Inch	Wt @29"		
<b>Group T1</b>					<b>Group T2</b>					<b>Group T3</b>					<b>Group T4</b>						
*920•1000R	0.920•1.000	A/C/E	5.8	168	*780•850R	0.780•0.850	A/C/E	6.0	174	*720•780R	0.720•0.780	A/C/E	6.4	186	*670•720R	0.670•0.720	A/C/E	5.9	171		
*900•1000R	0.900•1.000	X10	5.8	168	*750•830R	0.750•0.830	X10	6.4	186	*700•750R	0.700•0.750	X10	6.7	194	*650•700R	0.650•0.700	X10	6.8	197		
*880•1000R	0.880•1.000	Nav	5.5	160	*810•880R	0.810•0.880	Nav	5.8	168	*710•810R	0.710•0.810	Nav	6.3	183	*660•710R	0.660•0.710	Nav	6.6	191		
2L-04	1.020	A/C/C	6.1	177	2-04	0.920	A/C/C	6.5	189	3X-04	0.830	A/C/C	6.7	194	3L-04	0.750	A/C/C	7.0	203		
2-04	0.920	A/C/C	6.5	189	780	0.780	Rdln	6.3	183	3L-04	0.750	A/C/C	7.0	203	3-04	0.680	A/C/C	7.2	209		
900	0.900	Rdln	5.8	168	1812	0.879	X7	7.3	212	780	0.780	Rdln	6.3	183	690	0.690	Rdln	6.3	183		
1712	1.099	X7	6.7	194	1714	0.963	X7	8.1	235	1912	0.778	X7	7.6	220	1912	0.778	X7	7.6	220		
1713	1.044	75	7.4	215	1716	0.880	75	9.0	261	1813	0.874	75	7.9	229	2012	0.680	X7	8.0	232		
1714	0.963	X7	8.1	235						1814	0.799	X7	8.6	249	1913	0.733	75	8.3	241		
1616	1.079	75	8.4	244						1816	0.756	75	9.3	270	1914	0.658	X7	9.3	270		
<b>Group T5</b>					<b>Group T6</b>					<b>Group T7</b>					<b>Group T8</b>						
*620•670R	0.620•0.670	A/C/E	6.1	177	*570•620R	0.570•0.620	A/C/E	6.3	183	*520•570R	0.520•0.570	A/C/E	6.7	194	*470•520R	0.470•0.520	A/C/E	6.8	197		
*600•650R	0.600•0.650	X10	7.0	203	*550•600R	0.550•0.600	X10	7.5	218	*500•550R	0.500•0.550	X10	7.8	226	*450•500R	0.450•0.500	X10	8.1	235		
*610•660R	0.610•0.660	Nav	6.9	200	*540•610R	0.540•0.610	Nav	7.4	215	*540•610R	0.540•0.610	Nav	7.4	215	*480•540R	0.480•0.540	Nav	8.0	232		
3-04	0.680	A/C/C	7.2	209	500	0.500	AC Slim	8.5	247	500	0.500	AC Slim	8.5	247	500	0.500	AC Slim	8.5	247		
690	0.690	Rdln	6.3	183	3L-18	0.620	A/C/C	7.5	218	3-18	0.560	A/C/C	7.8	226	3-28	0.500	A/C/C	8.1	235		
2012	0.680	X7	8.0	232	600	0.600	Rdln	6.9	200	3-28	0.500	A/C/C	8.1	235	460	0.460	Rdln	7.3	212		
2013	0.610	75	9.0	261	500	0.500	LSpd	6.5	189	520	0.520	Rdln	7.1	206	500	0.500	LSpd	6.5	189		
1914	0.658	X7	9.3	270	500	0.500	FB	7.1	206	500	0.500	LSpd	6.5	189	500	0.500	FB	7.1	206		
1916	0.623	75	10.0	290	2112	0.590	X7	8.4	244	500	0.500	FB	7.1	206	2212	0.505	X7	8.8	255		
					2013	0.610	75	9.0	261	2212	0.505	X7	8.8	255	2114	0.510	X7, 75	9.9	287		
					2014	0.579	X7	9.6	278	2114	0.510	X7, 75	9.9	287	2115	0.461	75	10.8	313		
					1916	0.623	75	10.1	290	2016	0.531	75	10.6	307							
<b>Group T9</b>					<b>Group T10</b>					<b>Group T11</b>					<b>Group T12</b>						
*430•470R	0.430•0.470	A/C/E	7.0	203	*400•430R	0.400•0.430	A/C/E	7.5	218	*370•400R	0.370•0.400	A/C/E	7.9	229	370R	0.370	A/C/E	7.9	229		
*410•450R	0.410•0.450	X10	8.5	247	*380•410R	0.380•0.410	X10	8.9	258	380R	0.380	X10	8.9	258	340	0.340	AC Slim	10.7	310		
*430•480R	0.430•0.480	Nav	8.4	244	*430•480R	0.430•0.480	Nav	8.4	244	400	0.400	AC Slim	9.7	281	3-60	0.340	A/C/C	9.5	276		
400	0.400	AC Slim	9.7	281	400	0.400	AC Slim	9.7	281	3-49	0.390	A/C/C	8.8	255	3-71	0.300	A/C/C	9.9	287		
3-39	0.440	A/C/C	8.6	249	3-39	0.440	A/C/C	8.6	249	3-60	0.340	A/C/C	9.5	276	360	0.360	Rdln	8.3	241		
460	0.460	Rdln	7.3	212	3-49	0.390	A/C/C	8.8	255	360	0.360	Rdln	8.3	241	340	0.340	LSpd	8.2	238		
400	0.400	LSpd	7.4	215	410	0.410	Rdln	7.6	220	400	0.400	LSpd	7.4	215	340	0.340	FB	8.3	241		
400	0.400	FB	7.8	226	400	0.400	LSpd	7.4	215	400	0.400	FB	7.8	226	2512	0.321	X7	10.3	299		
2312	0.423	X7	9.5	276	400	0.400	FB	7.8	226	2413	0.365	X7, 75	10.5	305	2613	0.265	X7	11.5	334		
2213	0.460	X7, 75	9.9	287	2412	0.400	X7	9.7	281	2314	0.390	X7, 75	10.8	313							
2214	0.425	X7	10.4	302	2413	0.365	X7, 75	10.5	305	2315	0.340	X7, 75	11.8	342							
2115	0.461	75	10.8	313	2214	0.425	X7	10.4	302												
					2314	0.390	X7, 75	10.8	313												
<b>Group T13</b>					<b>Group T13</b>					<b>Group T13</b>					<b>Group T13</b>						
300	0.300	AC Slim	11.5	334	2613	0.265	X7	11.5	334	A/C/E	Aluminum/Carbon/Extreme					R	The size recommendations for recurve bows are indicated with a letter "R" next to the size.				
3-71	0.300	A/C/C	9.9	287						X10	X10 Shafts (Aluminum/Carbon)					Size	Indicates suggested arrow size				
2512	0.321	X7	10.3	299						Nav	Navigator (Aluminum/Carbon)					Spine	Spine of arrow size shown (static)				
2613	0.265	X7	11.5	334						AC Slim	Aluminum/Carbon Super Slim					Model	Designates arrow model				
										A/C/C	Aluminum/Carbon/Composite					Weight	Listed in grains per inch				
										Rdln	Redline										
										LSpd	LightSpeed										
										FB	FatBoy										
										X7	X7 Eclipse and Cobalt (7178-79 alloy)										
										75	XX75: Platinum Plus and Jazz (7075 alloy)										

\* When two sizes are listed together, the weight listed is for the first shaft.